

# Safety Data Sheet

## E-Panel®, epL-5™



Revision Date: 6/24/ 2019

Initial Release Date: 4/22/2010

Version 3.0

### Section 1. Product Identification

Product name: E-Panel®, epL-5™

Company Identification

3A Composites USA, Inc.  
208 W. 5<sup>th</sup> Street, P.O. Box 507  
Benton, KY 42025

Emergency Phone Number: (800) 872-8974

To be used only in the event of chemical emergencies involving a spill, leak, fire, and exposure accidents involving chemicals.

### Section 2. Hazard Identification

**Physical Appearance:** Medium weight rigid panel

**Potential Health Effects:**

This product is classified as a non-hazardous component when polymerized. Avoid breathing fumes if abraded, melted, welded, cut or processed.

**Ingestion:** Swallowing is not anticipated. If swallowed, seek immediate medical advice.

### Section 3. Chemical Composition

Ingredients:	CAS Number	Percent % (by weight) *
Polyethylene	9002-88-4	39-72
Aluminum <sup>3</sup>	7429-90-5	28-61

\*Concentration of ingredients depends upon thickness of material

### Section 4. First Aid Measures

These products are not considered to be a health hazard in the form in which they are sold (sheet, panel). However, if these products are abraded, melted, welded, cut or processed in any manner that causes release of fumes or dusts, hazardous levels of fumes or dusts may be generated from these products.

**Eye Contact:** Dust may mechanically irritate the eyes, resulting in redness or watering. Treat dust in eye as foreign object. Flush with water to remove dust particles. Get medical help if irritation persists.

**Skin Contact:** Not anticipated for product in purchased form, wash with mild soap and water.

**Inhalation:** If inhalation causes adverse effects, respirator selection, use and maintenance should be in accordance with the requirements of OSHA Respiratory Protection Standard, 29 CFR 1920.134. Remove to fresh air. Get medical help if persistent irritation, severe coughing or breathing difficulty occurs.

**Note to Physician:** No special advice, treat symptomatically

**Ingestion:** Not likely to occur for product in purchased form.

**Inhalation:** Excessive dust concentrations may cause unpleasant obstruction in the nasal passages.

**Skin Absorption:** Product is not absorbed through the skin.

# Safety Data Sheet

## E-Panel®, epL-5™



Revision Date: 6/24/ 2019

Initial Release Date: 4/22/2010

Version 3.0

### Section 5. Fire Fighting Measures

Extinguishing media: Water, foam, CO<sub>2</sub>, dry chemical powder

Special firefighting procedure: Toxic gases may form upon combustion. Respiratory protection is recommended.

### Section 6. Accidental Release

A release should not occur. However, if these products are abraded, melted or cut, dusts may be generated. Should a release of dusts occur, contain by blocking routes to surface water and grassy areas. Clean up by sweeping and depositing into a closed container.

### Section 7. Handling and Storage

Store in a flat dry area. Handle carefully to avoid scratching product finish. Caution should be taken to avoid sharp edges.

### Section 8. Exposure Controls

These products are not considered to be a health hazard in the form in which they are sold (sheet, panel). However, if these products are abraded, melted, welded, cut or processed in any manner that causes release of fumes or dusts, hazardous levels of fumes or dusts may be generated from these materials or constituents of these materials. Aluminum fumes or dust are subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372.

**RESPIRATORY PROTECTION** – Not required. However, use NIOSH-approved filtering face piece respirator (“dust mask”) and goggles where ventilation is limited. Use respiratory protection in accordance with regulatory requirements such as the OSHA respiratory protection standard 29 CFR 1910.134.

**PROTECTIVE GLOVES** – Not required. However, cloth, canvas, or leather gloves are recommended to minimize potential mechanical irritation or cuts from handling product.

**EYE PROTECTION** – Approved goggles or tight fitting safety glasses are recommended when exposures to dust may occur (e.g. during clean up) and when eye irritation may occur.

**OTHER PROTECTIVE CLOTHING OR EQUIPMENT** – Not applicable for product in purchased form. Outer garments may be desirable in extremely dusty areas.

**WORK/HYGIENE PRACTICES** – Follow good hygiene and housekeeping practices. Clean up areas where dust settles to avoid excessive accumulation. Minimize compressed air blow down or other practices that generate high airborne-dust concentrations.

**Ventilation:**

**LOCAL EXHAUST** – Provide local exhaust as needed so that exposure limits are met. Use with adequate ventilation to ensure exposure levels are maintained below the limits provided above. Use local exhaust ventilation, and process enclosure if necessary, to control airborne dust. Ventilation to control dust should be considered where potential explosive concentrations and ignition sources are present. The design and operation of any exhaust system should consider the possibility of explosive concentrations of cellulose dust within the system. See “SPECIAL” section below.

**MECHANICAL (GENERAL)** – Provide general ventilation in processing and storage areas so that exposure limits are met.

# Safety Data Sheet

## E-Panel®, epL-5™



Revision Date: 6/24/ 2019

Initial Release Date: 4/22/2010

Version 3.0

SPECIAL – Ensure that exhaust ventilation and material transport systems involved in handling this product contain explosion relief vents or suppression systems designed and operated in accordance with applicable standards if the operating conditions justify their use.

Ingredient	OSHA Exposure Limit		ACGIH
	Total	Respirable	TLV
Polyethylene	10mg/m <sup>3</sup>	5mg/m <sup>3</sup>	N.E.
Aluminum	15mg/m <sup>3</sup>	5mg/m <sup>3</sup>	N.E.

### Section 9. Physical and Chemical Properties

Appearance:	Solid sheet. Sandwich construction
Odor:	Not Applicable
Odor Threshold:	Not Applicable
PH:	Not Applicable
Melting Point:	Aluminum > 890 °F Core > 210 °F
Initial Boiling Point:	No Data
Flash Point:	Not Applicable
Evaporation Rate:	Not Applicable
Flammability:	Not Flammable
Upper/lower explosive limit:	Not Applicable
Vapor Pressure:	Not Applicable
Vapor Density:	Not Applicable
Specific Gravity:	Aluminum 2.70 – 2.73 g/ccm range. Core 1.5 – 1.7 g/ccm range.
Solubility:	Not Soluble
Partition coefficient:	Not Applicable
Auto-Ignition:	Composite – (ASTM D-1929) 768 °F, 409 °C
Decomposition Temperature:	No Data
Viscosity:	Not Applicable

### Section 10. Stability and Reactivity

<u>Stability:</u>	Stable
<u>Incompatibility:</u>	None known
<u>Decomposition products:</u>	May produce water, carbon monoxide, carbon dioxide, and smoke upon combustion.
<u>Conditions to avoid:</u>	None known

No information available at this time.

# Safety Data Sheet

E-Panel®, epL-5™



Revision Date: 6/24/ 2019

Initial Release Date: 4/22/2010

Version 3.0

## Section 12. Ecological Information

No information available at this time.

## Section 13. Disposal Information

Dispose of waste materials in accordance with Federal, State and local regulations


## Section 14. Transportation

DOT: Not regulated

IMDG: Not regulated

## Section 15. Regulatory Information

### **PROPOSITION 65: (California Only)**

Additional Requirements for the State of California: “ **WARNING:** This product can expose you to chemicals including Ethyl Benzene, which is known to the State of California to cause cancer. For more information, go to [www.P65Warnings.ca.gov](http://www.P65Warnings.ca.gov).”

*We realize that this warning sounds very alarming however; we want to reassure you based on the findings of reliable research. While there is research that supports health-related risks due to exposure to the listed chemical, this research also finds that the key factor in determining the health risk is the amount of exposure to the chemical vapors and not products made as a result of its use. These hazardous exposure limits are generally found in the workplace when chemicals in liquid form are being used, and are no longer in liquid forms in the products being shipped to our retailers and customers.*

**REACH:** Pursuant to Title II article 7 of the regulation this product is exempt from registration and notification and is therefore compliant with the REACH regulation.

**RoHS:** All current colors of Dibond are compliant with the RoHS standard with the exception of Hunter Red over Caution Yellow and Ultra Marine over Dark Green.

**TSCA:** All ingredients of this product are either listed on the TSCA Inventory or are exempt from TSCA Inventory requirements under 40 CFR 720.30.

**CERCLA:** This product does not contain ingredients which are subject to the reporting requirements of CERCLA.

**SARA 313 Information:** This product does not contain a chemical ingredient(s) with known CAS Number to exceed the *de minimis* reporting levels established by SARA Title III, section 313 and 40 CFR section 372 depending upon pulp inventory.

**SARA 311/312 Hazard Category:** This product has been reviewed according the EPA “Hazard Categories: promulgated under SARA Title III, Sections 311 and 312 and is considered, under applicable definitions, to meet the following categories:

An immediate acute) health hazard	No
A delayed (chronic) health hazard	No
A corrosive hazard	No
A fire hazard	No
A reactivity hazard	No
A sudden release hazard	No

## Section 16. Other Information

# Safety Data Sheet

E-Panel®, epL-5™



Revision Date: 6/24/ 2019

Initial Release Date: 4/22/2010

Version 3.0

**IMPORTANT:** The information and data contained herein are believed to be accurate and have been compiled from sources believed to be accurate. All information contained herein is offered for your consideration, information, investigation, and verification. 3A COMPOSITES MAKES NO WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, CONCERNING THE ACCURACY OR COMPLETENESS OF THE INFORMATION AND DATA HEREIN. THE IMPLIED WARRANTIES OF MERCHANTABILITY AND FITNESS FOR A PARTICULAR PURPOSE ARE SPECIFICALLY EXCLUDED. 3A Composites will not be responsible for claims relating to any parties' use of or reliance on information and data contained herein regardless of whether it is claimed that the information are inaccurate, incomplete, or otherwise misleading.

## Definition of Common Terms:

ACGIH	=	American Conference of Governmental Industrial Hygienists
CAS#	=	Chemical Abstracts System Number
CERCLA	=	Comprehensive Environmental Response, Compensation, and Liability Act
DOT	=	U. S. Department of Transportation
DSL	=	Domestic Substance List
EPA	=	U.S. Environmental Protection Agency
IARC	=	International Agency for Research on Cancer
IATA	=	International Air Transport Association
IMDG	=	International Maritime Dangerous Goods
NA	=	Not Applicable
NIOSH	=	National Institute for Occupational Safety and Health
NTP	=	National Toxicology Program
OSHA	=	Occupational Safety and Health Administration
PEL	=	Permissible Exposure Limit
REACH	=	Registration, Evaluation, Authorization and Restriction of Chemicals
RoHS	=	Restriction of Hazardous Substances used in electronic equipment
STEL	=	Short-Term Exposure Limit (15 minutes)
TDG	=	Canadian Transportation of Dangerous Goods
TLV	=	Threshold Limit Value
TSCA	=	Toxic Substance Control Act

End of Safety Data Sheet