


# THE Fabrication Guide



## FOME-COR® DISPA® SINTRA® GATOR® LUMEX® G DIBOND®

Quick reference sheet for possible fabrication methods for 3A products

	Mounting	Repositioning Vinyl	Digital Printing	Screen Printing	Painting	Knife Cutting	Saw Cutting	Routing	Die Cutting/Punching	Embossing	Forming Curves	Creasing
\$	<b>FOME-COR FOUNDATION (Acid-Free)</b>											
	◇ <sup>0</sup>					◇			◇	◇		
	<b>FOME-COR</b>											
	◇	◇	◇	◇	◇ <sup>3</sup>	◇			◇	◇		
	<b>FOME-COR w/ ENCORE Technology</b>											
	◇		◇	◇	◇ <sup>3</sup>	◇			◇			
	<b>FOME-COR SINGLESTEP (Heat-Activated)</b>											
	◇					◇			◇	◇		
	<b>FOME-COR CANVAS</b>											
			◇	◇	◇	◇			◇	◇		
	<b>FOME-COR JETMOUNT</b>											
	◇		◇	◇	◇ <sup>3</sup>	◇	◇	◇	◇	◇		
	<b>FOME-COR QUICKSTIK (Self-Adhesive)</b>											
	◇					◇			◇	◇		
	<b>DISPA</b>											
	◇		◇	◇	◇	◇		◇	◇		◇	◇
	<b>SINTRA CONSTRUCT</b>											
	◇ <sup>1</sup>	◇				◇ <sup>4</sup>	◇	◇	◇ <sup>5</sup>		◇	
	<b>SINTRA VERS</b>											
	◇ <sup>1</sup>	◇	◇	◇	◇	◇ <sup>4</sup>	◇	◇	◇ <sup>5</sup>		◇	
\$\$	<b>SINTRA</b>											
	◇ <sup>1</sup>	◇	◇	◇	◇	◇ <sup>4</sup>	◇	◇	◇ <sup>5</sup>		◇	
	<b>SINTRA ECLIPSE</b>											
	◇ <sup>1</sup>	◇	◇	◇	◇	◇ <sup>4</sup>	◇	◇	◇ <sup>5</sup>		◇	
	<b>GATORBLANKS</b>											
	◇					◇	◇	◇				
	<b>GATORPLAST</b>											
	◇	◇	◇	◇	◇ <sup>3</sup>	◇	◇	◇	◇ <sup>5</sup>			
	<b>GATORFOAM</b>											
	◇		◇	◇ <sup>2</sup>	◇ <sup>3</sup>		◇	◇				
	<b>GATORFOAM PRO</b>											
	◇		◇	◇ <sup>2</sup>	◇ <sup>3</sup>		◇	◇				
	<b>GATORFOAM EXTERIOR</b>											
	◇		◇	◇ <sup>2</sup>	◇ <sup>3</sup>		◇	◇				
	<b>GATORFOAM SELF-ADHESIVE</b>											
	◇	◇					◇	◇				
	<b>LUMEX G</b>											
	◇	◇	◇	◇	◇		◇	◇	◇		◇	
	<b>E-PANEL / EPL-5</b>											
	◇ <sup>1</sup>	◇	◇	◇	◇		◇	◇	◇ <sup>6</sup>			
\$\$\$	<b>DIBOND</b>											
	◇ <sup>1</sup>	◇	◇	◇	◇		◇	◇	◇ <sup>6</sup>		◇	

Trialing is recommended to ensure suitability for the proposed fabrication before full-scale commercialization.

- 0 Archival conservation mounting
- 1 Cold mounting techniques only

- 2
- 3
- 4
- 5
- 6

- Face priming will provide better results
- Do not expose polystyrene foam to solvent-based paints
- 1-3mm may be cut with a knife or blade
- May be die cut in gauges up to 5mm or 3/16"
- Punch press die set is required