

## PRODUCT DATA SHEET

# AXCENT™

### PRODUCT DESCRIPTION

AXCENT™ 0.040" thick flat aluminum sheet is excellent for any building project that requires metal trim details, including but not limited to drip edge and parapet coping for roof systems, sill, head, and jamb for curtain wall and window systems.

AXCENT™ materials give shape to your great ideas by offering the perfect finishing touch to projects clad in ALUCOBOND® PLUS.

### PRODUCT PROPERTIES

	AXCENT™
Properties	0.040"
Standard Width*	48.0"
Standard Length*	120.0"
Custom Length (minimums apply)	available in 64"- 192"
Weight	0.56 lb/ft <sup>2</sup>
Yield Strength	Minimum 19 ksi
Min. Bend Radius	2T
Brinell Hardness	40
Aluminum Alloy	3003, 3104, or 3105 aluminum coils per ASTM B209

\* width tolerance 0.00625"; length tolerance -0/+0.375"

### MASKING

Each sheet is tension leveled and shipped with removable masking that protects the sheets during transport and fabrication. All masking is suitable for laser cutting. The film should be removed as soon as possible after installation especially in areas of heat and sunlight.

### CARE and CLEANING

AXCENT™ sheets are coated with chemically inert coatings, the back side of the sheet is coated with an epoxy clear coat to help reduce the risk of corrosion. See [ALUCOBOND PLUS Material Cleaning Guide](#) for recommendations on cleaning AXCENT™ sheets.

Information contained herein, or related to, is intended for use at one's own discretion. Such information is believed to be reliable, but 3A Composites shall have no responsibility or liability for results obtained or damages resulting from such use. 3A Composites USA, Inc. does not make any warranties, expressed or implied.



ALUCOBOND® is a registered trademark of 3A Composites USA Inc.  
© 7.2025 3A Composites USA All Rights Reserved.

ALUCOBONDUSA.COM / 800.626.3365