

# GATOR-PLY®

## SYN-PLY®

## LUXCELL®



# PRODUCT SELECTION

PRODUCTS	THICKNESS	COLORS	DENSITY	DIMENSIONAL CHANGE	APPLIED	WEIGHT PER MSF (IN LBS)	RECOMMENDED USES	GREENGUARD CERTIFIED?
Gator-Ply - 306-04	.026"	Black	40 ~ 10%	< 1% MD/CD	Hot Cold	86.0 ~ 8.0	For use with .030 HPL, .050 HPL, with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	No
Gator-Ply - 301-05	.026"	Dark Brown	40 ~ 10%	< 1% MD/CD	Hot Cold	86.0 ~ 8.0	For use with .030 HPL, .050 HPL, with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	No
Gator-Ply - 304-04	.020"	Black	40 ~ 10%	< 1% MD/CD	Hot Cold	66.5 ~ 6.5	For use with .030 HPL, with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply or 5-ply construction hot/cold press	No
Gator-Ply - 304-05	.020"	Dark Brown	40 ~ 10%	< 1% MD/CD	Hot Cold	66.5 ~ 6.5	For use with .030 HPL, with straight grain wood veneer, and in 3-ply construction hot/cold press	No
Gator-Ply - 304-08	.020"	Tan	40 ~ 10%	< 1% MD/CD	Hot Cold	66.5 ~ 6.5	For use with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	No
Gator-Ply - 308-04	.016"	Black	40 ~ 10%	< 1% MD/CD	Hot Cold	56.0 ~ 7.0	For use with .030 HPL, with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply or 5-ply construction hot/cold press	No
Gator-Ply - 308-09	.016"	Dark Brown	40 ~ 10%	< 1% MD/CD	Hot Cold	56.0 ~ 7.0	For use with .030 HPL, with straight grain wood veneer, with fancy face veneer, with reconstituted wood veneer, and in 3-ply or 5-ply construction hot/cold press	No
Green Gator - 304-19	.020"	Black	40 ~ 10%	< 1% MD/CD	Hot Cold	66.5 ~ 6.5	For use with .030 HPL, with straight grain wood veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	Yes
Green Gator - 308-19	.016"	Black	40 ~ 10%	< 1% MD/CD	Hot	56.0 ~ 7.0	For use with .030 HPL, with straight grain wood veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	Yes
Green Gator - 306-19	.024"	Black	40 ~ 10%	< 1% MD/CD	Hot Cold	86.0 ~ 8.0	For use with .030 HPL, with straight grain wood veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	Yes
Green Gator - 304-25	.020"	Dark Brown	40 ~ 10%	< 1% MD/CD	Hot Cold	66.5 ~ 6.5	For use with .030 HPL, with straight grain wood veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	Yes
Green Gator - 308-25	.016"	Dark Brown	40 ~ 10%	< 1% MD/CD	Hot Cold	56.0 ~ 7.0	For use with .030 HPL, with straight grain wood veneer, with reconstituted wood veneer, and in 3-ply construction hot/cold press	Yes
Luxcell - 112-05	.026"	White	40 ~ 10%	< 1% MD/CD	Hot Cold	97.0 ~ 8.0	For use in 3-ply or 5-ply construction hot/cold press	No
Luxcell - 103-08	.026"	Tan	40 ~ 10%	< 1% MD/CD	Hot Cold	94.0 ~ 8.0	For use in 3-ply or 5-ply construction hot/cold press	No
Syn-Ply - 206-06	.026"	Almond	40 ~ 10%	< 1% MD/CD	Hot	96.0 ~ 8.0	For use with crossband in 5-ply construction hot/cold press	No